

Backup Camera



130° Backup Camera With 18 Infra-Red Illuminators

RVS-770

The RVS-770 boasts a 410,000 pixel 2.5 mm lens with 18 infra-red illuminators which enable you to see in total darkness and a built-in microphone. The standard camera includes a 66' weatherproof cable with aircraft grade connectors. The RVS-770 is completely weatherproof with an IP69K rating and shock resistant with a 20G vibration and 100G impact rating.



■ WATERPROOF – IP69K RATING

The RVS-770 is completely waterproof with an IP69K rating, uniquely suited to all weather conditions.

■ INFRA-RED NIGHT VISION

With 18 infra-red lights, the backup camera will be able to see up to 50ft in complete darkness

■ 130° VIEWING ANGLE

With an ultra-wide viewing angle, the backup camera will provide a complete view from behind your vehicle. This ensures complete safety with no blind spots.

■ BUILT-IN HIGH GAIN MIC

The backup camera has a built-in microphone and will transmit audio directly to the system monitor

■ COMMERCIAL GRADE

This color CCD camera is built with heavy-duty zinc metal which encases the 2.5 mm Sharp lens.



Rear View Safety, 1797 Atlantic Ave., Brooklyn NY 11233
800.764.1028 sales@rearviewsafety.com
www.rearviewsafety.com

844.258.8178
safefleet.net



Backup Camera



130° Backup Camera With 18 Infra-Red Illuminators

RVS-770



Camera Specs	
Type	1/3" Sharp® Color CCD
Picture Elements	410,000 pixels
Gamma Correction	r=0.45 to 1.0
Image Sensor	620 TV lines
Lens	F=2.5mm
Pixels	NTSC: 811(h) X 507(v) PAL:752(H) X 582(V)
View Angle	130°
Waterproof Rating	IP69K
Sync System	Internal Synchronization
Infra-red distance	50 Feet (18 Infrared IR)
Usable Illumination	0 Lux (IR On)
Power Source	DC 12V
S/N Ratio	1/50, 160-1/100,000sec
Video Output	1Vp.p 75 ohm
IR Switch Control	ACDS Automatic Control
Vibration and Impact Rating	20G Vibration / 100G Shock
Operating Temperature	-40°C - +70°C (-40°F - +158°F) / RH 95% Max
Storage Temperature	-40°C - +85°C (-40°F - +185°F) / RH 95% Max
Net Weight	22oz
Dimensions	H: 3.25" W: 3"